

PA SYSTEM / SPEAKERS / CEILING

SKY-8

8" LOW IMPEDANCE CEILING LOUDSPEAKER



IP44


 SALT MIST
RESISTANCE

 3-POINT
ANCHORAGE


ANTI-DROP SYSTEM


 TAP-LOCK
TERMINALS

 TURN-LOOKABLE
GRILLE

- ✓ 8" double cone speaker. 20 W RMS@8 Ω
- ✓ Low profile aluminium grille
- ✓ Highly conductive quick-connect terminals
- ✓ Anti-fall system for installation assistance



+ Info:
<https://fonestar.com/SKY-8>

ESPECIALLY RECOMMENDED IN:



Hospitality



Retail



Hotels



All sectors

DESCRIPTION

Robust and versatile design for quality installations

The SKY-8 is a low impedance ceiling loudspeaker designed for high quality sound and functional design. Its frameless, low-profile grille, made of rust-resistant aluminium, provides a modern, unobtrusive aesthetic, ideal for any space. In addition, it can be customised thanks to its removable, paintable design without visible logo.

Maximum acoustic performance with easy installation

The SKY-8 combines power and precision in its performance:

Power: up to 27 W maximum with a wide frequency response of 40-15,000 Hz.

8" polypropylene cone: double diaphragm for greater fidelity.

Advanced protection: IP-44 rated against dust and water, suitable for demanding conditions.

In addition, installation is simple and safe:

Highly conductive quick-connect terminals.

Anti-fall system and hooks for safety cables.

Stable mounting brackets ensure reliable mounting.

Why choose SKY-8?

Designed for professional installers, the SKY-8 is ideal for projects that demand:

Reliability: durable materials such as ABS with UV resistance and aluminium with anti-corrosion paint.

Adaptability: paintable design to suit any environment.

Precise acoustic coverage: defined angles for optimal sound dispersion indoors.

The SKY-8 guarantees a perfect balance between aesthetics, functionality and durability, making it an outstanding solution for commercial and industrial applications.



+ Info:

<https://fonestar.com/SKY-8>

TECHNICAL CHARACTERISTICS

FEATURES	<p>Low impedance ceiling loudspeaker.</p> <p>Low profile frameless grille, constructed from rust resistant aluminium. Detachable, turn-lockable grille. The logo can be removed and painted.</p> <p>Fast connection terminals and high conductivity.</p> <p>Anti-fall system for installation assistance.</p> <p>Hook for safety cable.</p> <p>Stable, worm-gear ceiling brackets.</p> <p>Protection against dust and water.</p>
POWER	<p>20 W RMS</p> <p>27 W MAX.</p>
SPEAKER	8" polypropylene double cone diaphragm
RESPONSE	<p>40-15,000 Hz @ -10 dB</p> <p>90-15,500 Hz @ -3 dB</p>
IMPEDANCE	8 Ohm
SENSITIVITY	88 dB @ 1 W/1 m
SOUND PRESSURE	<p>103 dB @ max. W/1m Continuous</p> <p>105 dB @ max. W/1m Peak</p>
COVERAGE ANGLE:	H/V (-6 dB): 70°@500Hz, 90°@1kHz, 70°@2kHz, 50°@4kHz
PROTECTIONS	<p>IP-44 in compliance with IEC 60529</p> <p>EN ISO 9227:2006 Neutral Salt Spray Test</p>
MATERIAL	<p>ABS (UV resistant)</p> <p>Liquid painted aluminium grille</p>
CONNECTORS	<p>Highly conductive quick-connect terminals</p> <p>For cable cross-section 0.4 ~ 4 mm².</p>
OPERATION TEMPERATURE	-20°C ~ 70°C (48 h)
STORAGE TEMPERATURE	10°C ~ 40°C
MAXIMUM HUMIDITY	95%
COLOUR	White (RAL 9003)
DIMENSIONS	<p>Total loudspeaker: 306 mm Ø x 114 mm height</p> <p>Grille section: 7 mm</p> <p>Recessed height: 107 mm</p> <p>Installation hole: 273 mm Ø</p> <p>Maximum ceiling thickness: 30 mm</p>
WEIGHT	1.3 kg
ACCESSORIES	Installation template



+ Info:
<https://fonestar.com/SKY-8>