

AUDIO AND CONSUMER ELECTRONICS / AUXILIARY EQUIPMENT / CONVERTERS

FO-42DAV

DIGITAL TO ANALOGUE AUDIO CONVERTER





High audio quality



Optical (Toslink) or RCA digital input for connecting TV or digital player output.



Simultaneous headphone and amplification output.



Volume control



Bass setting

ESPECIALLY RECOMMENDED IN:







Education



Offices



All sectors



+ Info:

https://fonestar.com/FO-42DAV

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



DESCRIPTION

Digital to analogue audio converter with headphone output and volume controlThe FO-42DAV digital-to-analogue audio converter converts the digital, Toslink or coaxial audio input signal from a TV or digital player into an analogue audio signal for connecting stereo headphones and an external amplifier at the same time. It delivers high quality audio. Converts optical or coaxial SPDIF PCM digital audio format to stereo L/R analogue outputs. It supports the most common sampling rates up to 192 kHz, with up to 24-bit resolution. High fidelity design using new D/A converter chips. Allows control of bass and output volume adjustment. High-strength, anti-interference metal enclosure. Quick installation with plug and play. For domestic and professional use.

TECHNICAL CHARACTERISTICS

FEATURES	Digital audio to analogue converter. Simultaneous headphone and line output for amplifier. Volume control. Bass setting. PCM/LPCM SPDIF stereo format. 16-24 bit, 44.1 KHz, 48 KHz, 96 KHz and 192 KHz DACs
INPUTS	Optical stereo SPDIF, toslink 32-192 kHz Coaxial stereo SPDIF, RCA 32-192 kHz
OUTPUTS	Stereo audio, 2 x RCA TRS 3.5 mm jack, headphones,
CONTROLS	Volume control Bass setting
POWER SUPPLY	5 V DC, 1 A, via Micro USB port, with adapter included
DIMENSIONS	72 x 19 x 80 mm depth
WEIGHT	0.11 kg
ACCESSORIES	USB to Micro USB power cable and adapter, 70 cm



+ Info:

https://fonestar.com/FO-42DAV