CAVO SICUREZZA 1 X 0,08 (75) + 2 X 0,50 MM² - NERO - 100 M



Cavo video speciale - 1x0,08 (75Ω) +2x0,50 mm²

Per applicazioni di videosicurezza, sicurezza e videocamere.

Reference: C226

Guaina in PVC morbido ignifugo nero.

Cavo esterno Diam. Ø 6,60 (± 0,20) mm.

75 Ω Video Coax:

Guaina interna in PVC ignifugo.

Diam. Ø 2,80 (± 0,20) mm.

Schermatura a spirale in rame stagnato O.F.C. copertura 100%.

Dielettrico in PEE bianco. Diam. Ø 1,50 (± 0,20) mm.

Formazione di rame rosso O.F.C. a trefoli 10x0,10 mm.

Nom. Sezione 1x0,08 mm²

Nuclei isolati:

Guaine interne in PVC ignifugo.

Entrambi di colore nero. Diam. Ø 1,90 (± 0,20) mm.

Formazioni a trefoli 16x0,20 mm, un conduttore in rame stagnato O.F.C. e uno in rame rosso. Nom. Sezione 2x0,50 mm².

Proprietà:

Insulated Conductors Resistance 38,00 Ω/Km

Coax Conductor Resistance 203 Ω/Km

Coax Capacity Core/Shield 67 pF/m

Coax Velocity of Propagation 66%

Coax Impedance 75 Ω

Max Rated Voltage 49V

Operative Temperature -20/+70°C

Coaxial Properties Attenuation dB/100 m:

50 MHz 19,50

100 MHz 28,50

200 MHz 41,70

400 MHz 60,20

800 MHz 87,30

1000 MHz 103,00

RoHS2 Compliant: Ver. B / 26.05.19