CASSA PASSIVA 160W, 8X3" IN ALLUMINIO 100V FULL RANGE COLORE BIANCO



Sistema passivo

Custodia in alluminio estruso

Altoparlante full range 8 x 3”, 3PN16

Dispersione H x V: 120º x 20º

Picco SPL: 123 dB

Trasformatore multipresa 100/70V incluso

Funzionamento a bassa/alta impedenza

Reference: Q-83-TW

Questo sistema è progettato per locali di piccole e medie dimensioni. La stretta dispersione verticale (20º) impedisce l'uscita del campo di riverbero, migliorando l'intelligibilità in spazi come centri culturali, musei, sale conferenze... il tutto offrendo una riproduzione musicale superba.

La struttura in alluminio e il kit IP-66 ne fanno una scelta altamente affidabile e resistente, disponibile in qualsiasi colore RAL.

Performance	
Frequency Range (-10 dB)	150 Hz – 20 kHz
Horizontal Coverage (-6 dB)	120º
Vertical Coverage	20º
Nominal Impedance	8 ohms
Transformer Taps 70 V	12.5 W – 25 W – 50 W
Transformer Taps 100 V	25 W – 50 W – 100 W
RMS Power Handling	160 W
Peak Power Handling	640 W
On-axis Sensitivity 1W/1 m	95 dB SPL
Maximum Peak SPL at 1 m	123 dB SPL
Recommended Processor	DSP-226
Connectors	
Audio Input Connector	Ceramic Barrier Strip Terminals
Enclosure	
Enclosure Construction	Aluminum
Color	White

IP Rating	IP66
Depth	130 mm (5,1 in)
Dimensions (H x W x D)	685 x 125 x 130 mm 27,0 x 4,9 x 5,1 in
Net Weight	7,8 kg (17,2 lb)